

Ver.1.0

Diagonal 5.81 mm (Type 1/3.1) CMOS Solid-state Image Sensor with Square Pixel for Monochrome Cameras

Description

The IMX900-AMR is a diagonal 5.81mm (Type 1/3.1) CMOS active pixel type solid-state image sensor with a square pixel array and 3.20 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with 2.9 V, 1.8 V, 0.8 V power supply. High sensitivity and low dark current characteristics are achieved.

(Applications: FA cameras, Code reading cameras, Embedded vision systems)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency 24 MHz (only for CSI-2) / 37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 2048 (H) × 1536 (V) approx. 3.14 M pixels
- ◆ Readout mode
 - All-pixel scan mode
 - Vertical / Horizontal 1/2 Subsampling mode
 - 2 x 2 average mode
 - Vertical 1/10 Subsampling mode
 - ROI mode
 - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in All-pixel scan mode: 8-bit 125.1 frame/s, 10-bit 117.0 frame/s, 12-bit 72.0 frame/s
- ◆ Variable-shutter speed (1 H unit step)
- ◆ Pulse Output Function
 - The monitor output for Exposure period (GPO0, GPO1, GPO2)
- ◆ 8-bit / 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
 - 0 dB to 24 dB: Analog Gain (0.1 dB step)
 - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
 - SLVS (2 ch / 4 ch) output
 - CSI-2 (1 Lane / 2 Lane / 4 Lane) output
- ◆ CRA characteristics
 - The target CRA is 8 degree at 100% image height

Pregius S

* Pregius S and its logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates. Pregius S is a global shutter sensor technology for active pixel-type CMOS image sensors. By stacking the signal processing on the back illuminated type CMOS Image Sensor it realizes small chip size and high sensitivity, whilst using the high picture quality global shutter pixel technology of Pregius.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

◆ CMOS image sensor		
◆ Image size	Diagonal 5.81 mm (Type 1/3.1)	Approx. 3.20 M pixels
◆ Total number of pixels	2064 (H) × 1592 (V)	Approx. 3.28 M pixels
◆ Number of effective pixels	2064 (H) × 1552 (V)	Approx. 3.20 M pixels
◆ Number of active pixels	2064 (H) × 1552 (V)	Approx. 3.20 M pixels
◆ Number of recommended recording pixels	2048 (H) × 1536 (V)	Approx. 3.14 M pixels
◆ Unit cell size	2.25 μm (H) × 2.25 μm (V)	
◆ Optical black	Horizontal (H) direction: Front 0 pixels, rear 0 pixel Vertical (V) direction: Front 40 pixels, rear 0 pixel	
◆ Package	114 pin LGA	12.0 mm (H) × 9.3 mm (V)

Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	3298 LSB/lx/s	
Saturation signal	Min.	1022 LSB	

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel mode	2048 (H) × 1536 (V) Approx. 3.14 M pixels	114.0	SLVS 4 ch	8
		125.1	CSI-2 4 Lane	
		93.8	SLVS 4 ch	10
		117.0	CSI-2 4 Lane	
		72.0	SLVS 4 ch	12
		72.0	CSI-2 4 Lane	
1/2 subsampling mode 2 × 2 average mode	1024 (H) × 768 (V) approx. 0.78 M pixels	348.0	SLVS 4 ch	8
		396.5	CSI-2 4 Lane	
		297.6	SLVS 4 ch	10
		376.3	CSI-2 4 Lane	
		249.4	SLVS 4 ch	12
		249.4	CSI-2 4 Lane	
Vertical 1/10 subsampling mode	2048 (H) × 154 (V) approx. 0.31 M pixels	620.4	SLVS 4 ch	8
		655.7	CSI-2 4 Lane	
		544.1	SLVS 4 ch	10
		631.5	CSI-2 4 Lane	
		452.4	SLVS 4 ch	12
		452.4	CSI-2 4 Lane	

Note: Figures are subject to change without notice.

